

TOYO TIRES®

OPEN COUNTRY M/T®

A REVOLUTIONARY, ALL-AROUND LIGHT TRUCK TRACTION RADIAL

The Open Country M/T is designed for full-size pickups driven by enthusiasts who require extra ground clearance, load-carrying capacity and off-road capability with great on-road performance.

Typical Vehicle Matches

Full-size trucks



Customer Benefit	Product Features	
All-Around Traction	<ul style="list-style-type: none"> • Aggressive, Attack Tread Design™ with Hook-Shaped Blocks • Scalloped Shoulder Blocks • M&S Rated 	<ul style="list-style-type: none"> • Tread Block Stabilizers • Deep Siping in the Tread Blocks • Open Shoulder Design
Styling	<ul style="list-style-type: none"> • Aggressive, Attack Tread Design™ • Over-the-Shoulder Tread • Open Shoulder Design 	<ul style="list-style-type: none"> • Black Outline Serrated Lettering • Rim Protector in Lower Sidewall
On-/Off-Road Handling	<ul style="list-style-type: none"> • T-Mode™ Technology • High Turn-Up, 3-Ply Casing • Two Wide Steel Belts 	<ul style="list-style-type: none"> • Two Spiral Wound Nylon Cap Plies • High Bead Filler
Traction Performance	<ul style="list-style-type: none"> • Aggressive, Attack Tread Design™ • Over-The-Shoulder Tread • Cap/Base Construction 	<ul style="list-style-type: none"> • Tread Block Stabilizers • Open, Scalloped Shoulder Blocks • Deep Siping in the Tread Blocks
Stable Ride	<ul style="list-style-type: none"> • T-Mode™ Technology • Computer-Optimized Tread Design • Advanced Production Technology for High Levels of Uniformity 	<ul style="list-style-type: none"> • Tread Elements Shaped and Staggered for Reduced Noise • 3-Ply Polyester Casing • Single Strand, Jointless Bead Wire Construction
Long Life	<ul style="list-style-type: none"> • High Turn-Up, 3-Ply Polyester Casing • Two Spiral Wound Nylon Cap Plies • Two Wide Steel Belts 	<ul style="list-style-type: none"> • Cap/Base Construction • Abrasion Resistant Sidewall Compound

LIGHT TRUCK/SUV

TOYO TIRES®

OPEN COUNTRY M/T®



Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (1/32")	Inflated Dimensions		Static Loaded Radius (inch)	Max. Load (lbs.)	Max. Pressure (PSI)	Revs Per Mile	Construction		Price
					O.A.D. (inch)	O.A.W. (inch)					Tread	Sidewall	
31X10.50R15LT 109Q C/6	360490	7.0-8.5-9.0	55	19.1	31.1	10.7	14.4	2270	50	667	3P+2S+2N	3P	
LT235/85R16 120/116P E/10	360440	6.0-6.5-7.5	52	18	32.0	9.4	14.9	3042	80	648	3P+2S+2N	3P	
LT255/85R16 123/120P E/10	360460	6.5-7.0-8.0	60	19	33.5	10.2	15.6	3415	80	619	3P+2S+2N	3P	
LT245/75R16 120/116P E/10	360450	6.5-7.0-8.0	52	18	30.7	9.9	14.3	3042	80	674	3P+2S+2N	3P	
LT265/75R16 123P E/10	360320	7.0-7.5-8.0	58	19	31.8	10.8	14.8	3415	80	651	3P+2S+2N	3P	
LT285/70R16 114P C/6 † (32X11.00R16)	360170	7.5-8.5-9.5	61	18.9	32.0	11.1	14.9	2600	50	648	3P+2S+2N	3P	
LT265/70R17 121P E/10	360130	7.0-8.0-8.5	63	19	32.0	10.8	14.9	3195	80	648	3P+2S+2N	3P	
LT275/70R18 125P E/10	360120	7.0-8.0-8.5	66	19	33.6	11.0	15.6	3640	80	617	3P+2S+2N	3P	
LT275/65R20 126P E/10	360410	7.5-8.0-9.5	71	19	34.5	11.0	16.0	3750	80	601	3P+2S+2N	3P	
33X10.50R15LT 114P C/6	360470	7.0-8.5-9.0	57	19	32.8	10.9	15.2	2600	50	632	3P+2S+2N	3P	
33x12.50R15LT 108P C/6	360100	8.0-10.0-11.0	73	21	33.0	12.8	15.4	2205	35	628	2P+2S+2N	3P	
33X13.50R15LT 109Q C/6	360290	8.5-11.0	75	21	33.1	13.9	15.4	2270	35	628	3P+2S+2N	3P	
LT285/75R16 126P E/10 (33X11.50R16)	360280	7.5-8.0-9.0	68	19	33.0	11.6	15.4	3740	80	628	3P+2S+2N	3P	
LT305/70R16 124P E/10 (33.0X12.0R16)	360110	8.0-9.0-9.5	72	20	33.0	12.2	15.4	3525	65	628	3P+2S+2N	3P	
LT285/75R17 121P E/10	360430	7.5-8.0-9.5	71	19	34.1	11.6	15.8	3195	80	608	3P+2S+2N	3P	
LT295/70R17 128P E/10 (33X11.50R17)	360360	8.0-8.5-9.5	73	19	33.5	11.9	15.6	3970	80	619	3P+2S+2N	3P	
33X12.50R18LT 118Q E/10	360340	8.5-10.0-11.0	75	21	33.0	12.7	15.3	2910	65	630	3P+2S+2N	3P	
33X12.50R20LT 114Q E/10	360330	8.5-10.0-11.0	72	21	33.0	12.6	15.3	2600	65	630	3P+2S+2N	3P	
35X13.50R15LT 114Q C/6	361000	8.5-11.0	84	21	34.8	14.4	15.2	2600	35	596	3P+2S+2N	3P	
LT315/75R16 127Q E/10 (35X12.50R16)	360230	8.0-8.5-10.0	76	21	34.9	12.9	16.2	3860	65	595	3P+2S+2N	3P	
35X12.50R17LT 125Q E/10	360310	8.5-10.0-11.0	83	21	34.8	13.2	16.2	3640	65	596	3P+2S+2N	3P	
LT285/75R18 129P E/10	360420	7.5-8.0-9.5	71	19	35.1	11.6	16.3	4080	80	591	3P+2S+2N	3P	
35X12.50R18LT 123Q E/10	360090	8.5-10.0-11.0	81	21	35.0	13.2	15.6	3415	65	593	3P+2S+2N	3P	
35X12.50R20LT 121Q E/10	360240	8.5-10.0-11.0	80	21	35.0	13.0	16.3	3195	65	592	3P+2S+2N	3P	
37X14.50R15LT 120Q C/6	360260	10.0-12.0	94	21	36.7	15.6	17.0	3080	35	566	3P+2S+2N	3P	
37X13.50R17LT 131Q E/10	360270	8.5-11.0	93	21	37.0	14.6	17.2	4300	65	560	3P+2S+2N	3P	
37X13.50R18LT 124Q D/8	360300	8.5-11.0	93	21	37.0	14.2	17.2	3525	50	560	3P+2S+2N	3P	
37X13.50R20LT 127Q E/10	360220	8.5-11.0	94	21	37.0	14.0	17.2	3860	65	560	3P+2S+2N	3P	
37X13.50R22LT 123Q E/10	360210	8.5-11.0	90	21	37.0	14.0	17.2	3420	65	560	3P+2S+2N	3P	
37X13.50R24LT 120Q E/10	360350	8.5-11.0	89	21	37.0	13.6	17.2	3085	65	561	3P+2S+2N	3P	
38X14.50R16LT 129Q D/8*	360250	10.0-12.0	99	21	37.7	15.6	17.5	4080	50	550	3P+2S+2N	3P	
38x13.50R18LT 126Q D/8*	360380	8.5-11.0	97	21	37.7	14.3	17.5	3750	50	550	3P+2S+2N	3P	
38X15.50R18LT 128Q D/8*	360180	11.0-12.0-13.0	106	21	37.7	15.9	17.5	3970	50	550	3P+2S+2N	3P	
38X13.50R20LT 124Q D/8*	360390	8.5-11.0	100	21	37.7	14.3	17.5	3525	50	550	3P+2S+2N	3P	
38X15.50R20LT 125Q D/8*	360190	11.0-12.0-13.0	101	21	37.7	15.9	17.5	3640	50	550	3P+2S+2N	3P	
40X15.50R20LT 130Q D/8*	360370	11.0-12.0-13.0	112	21	39.7	15.9	18.4	4190	50	522	3P+2S+2N	3P	
40X15.50R22LT 127Q D/8*	360200	11.0-12.0-13.0	110	21	39.7	15.9	18.5	3860	50	522	3P+2S+2N	3P	

Call Toyo Tires for current information. **Bold** designates measuring rim width. All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.

Construction Elements

Tread: 3P = 3-Ply Polyester Casing, 2S = 2 Steel Belts, 2N = 2 Nylon Cap Plies **Sidewall:** 3P = 3 Ply Polyester

*Specialty sizes for extreme off-road use where maximum ground clearance, or low ground contact pressure is required.

†Please note: Product code 360170 has a modified tread pattern as compared to standard OPMT.

See Toyo Safety Advisory for Lifted Light Trucks, Page 48



LIGHT TRUCK/SUV