

TOYO TIRES®

PROXES® TPT™ TOTAL PERFORMANCE TOURING RADIAL

The all-season Proxes TPT is the ideal performance touring replacement for modern cars equipped with T, H or V speed-rated tires as Original Equipment. Optimized casing design and a unique directional tread combine to provide wet and dry grip and handling with improved ride comfort and long treadlife.

Typical Vehicle Matches

Acura 3.2 TL; Audi; BMW; Cadillac STS;
Chrysler Sebring; Honda Accord; Infiniti;
Lexus ES, LS, SC, GS; Mazda 6; Mercedes-Benz;
Nissan Altima, Maxima; Pontiac Bonneville;
Grand Prix GTP; Toyota Avalon, Camry;
Volkswagon Jetta, Passat; Volvo.

Typical Customer Matches

Discriminating, style-conscious buyers upgrading from Original Equipment touring tires

Competitive Products

- BFGoodrich Traction T/A
- Goodyear Eagle ResponsEdge
- Michelin Pilot Exalto A/S
- Yokohama Avid H4s
- Yokohama Avid V4s



UTQG
400 A A

WARRANTY
T and H-Rated sizes:
60,000-mile treadwear
limited warranty.
V-Rated sizes: 40,000-mile
treadwear limited warranty.

Customer Benefit	Product Features
Handling	<ul style="list-style-type: none"> • High-modulus bead filler • Jointless, spiral-wound nylon cap and edge ply (construction may vary by size) • T-Mode™ Design Technology • Center rib designed for straight line stability • T, H and V speed-rated
Wet Traction	<ul style="list-style-type: none"> • Well-balanced sipes for wet traction • Unidirectional tread for improved aquaplaning resistance
All-Season Traction	<ul style="list-style-type: none"> • Unidirectional, touring-performance, all-season tread design • Aggressive siping • Optimized tread groove shape and angle • M&S rated
Smooth, Comfortable Ride	<ul style="list-style-type: none"> • T-Mode Design Technology • Strong polyester casing • Low-noise tread design • Jointless, spiral-wound nylon cap and edge ply (construction may vary by size)
Style	<ul style="list-style-type: none"> • High-image sidewall styling with stylized lettering • Unidirectional tread design
Long Treadlife	<ul style="list-style-type: none"> • Two full-width steel belts • Cap/base tread compound • 400 UTQG Treadwear rating

PERFORMANCE

PROXES® TPT™ TOTAL PERFORMANCE TOURING RADIAL



Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (32")	Inflated Dimension		Static Loaded Radius (inch)	Max. Load (lbs.)	Max. Pressure (PSI)	Revs Per Mile	Price
					Overall Diameter (inch)	Overall Width (inch)					
P195/70R14 90H	187680	5.0-6.0-6.5	19	11	24.8	7.9	11.2	1312	44	838	
185/65R14 86H	187840	5.0-5.5-6.5	16	10	23.3	7.2	10.6	1168	44	890	
P185/60R14 82H	187500	5.0-5.5-6.5	16	10	22.8	7.4	10.4	1047	44	918	
P195/60R14 85H	187510	5.5-6.0-7.0	17	10	23.2	7.9	10.6	1135	44	899	
185/65R15 88H	187620	5.0-5.5-6.5	17	10	24.5	7.4	11.1	1235	44	855	
195/65R15 91H	187630	5.5-6.0-7.0	19	10	25.0	7.9	11.3	1356	44	836	
195/65R15 91V	187780	5.5-6.0-7.0	19	10	25.0	7.9	11.3	1356	44	836	
205/65R15 94H	187640	5.5-6.0-7.5	19	10	25.5	8.2	11.5	1477	44	822	
205/65R15 94V	187660	5.5-6.0-7.5	20	10	25.5	8.2	11.5	1477	44	822	
P215/65R15 95H	187670	6.0-6.5-7.5	21	10	26.0	8.7	11.7	1510	44	803	
195/60R15 88H	187520	5.5-6.0-7.0	18	10	24.2	7.9	11.0	1235	44	862	
195/60R15 88V	187800	5.5-6.0-7.0	18	10	24.2	7.9	11.0	1235	44	862	
205/60R15 91H	187530	5.5-6.0-7.5	20	10	24.7	8.2	11.2	1356	44	847	
205/60R15 91V	187540	5.5-6.0-7.5	21	10	24.7	8.2	11.2	1356	44	847	
P215/60R15 93H	187550	6.0-6.5-7.5	21	10	25.2	8.7	11.4	1433	44	830	
225/60R15 96H	187560	6.0-6.5-8.0	23	11	25.6	9.0	11.6	1565	44	814	
225/60R15 96V	187570	6.0-6.5-8.0	23	11	25.6	9.0	11.6	1565	44	814	
195/55R15 85V	187410	5.5-6.0-7.0	18	10	23.4	7.9	10.7	1135	44	890	
205/65R16 95H	187700	5.5-6.0-7.5	22	10	26.5	8.2	12.0	1521	44	789	
P205/60R16 91V	187580	5.5-6.0-7.5	21	10	25.7	8.2	11.7	1356	44	813	
215/60R16 95V	187690	6.0-6.5-7.5	23	10	26.1	8.7	11.9	1521	44	797	
225/60R16 98H	187590	6.0-6.5-8.0	25	11	26.6	9.0	12.1	1653	44	784	
225/60R16 98V	187600	6.0-6.5-8.0	25	11	26.6	9.0	12.1	1653	44	784	
235/60R16 100H	187610	6.5-7.0-8.5	26	11	27.1	9.5	12.3	1764	44	766	
205/55R16 94H RD	187450	5.5-6.5-7.5	21	10	24.9	8.4	11.4	1477	50	839	
205/55R16 94V RD	187460	5.5-6.5-7.5	21	10	24.9	8.4	11.4	1477	50	839	
215/55R16 93H	187470	6.0-7.0-7.5	21	10	25.3	8.9	11.6	1433	44	826	
215/55R16 93V	187810	6.0-7.0-7.5	21	10	25.3	8.9	11.6	1433	44	826	
225/55R16 95H	187480	6.0-7.0-8.0	24	10	25.8	9.2	11.8	1521	36	811	
225/55R16 95V	187490	6.0-7.0-8.0	25	10	25.8	9.2	11.8	1521	36	811	
195/50R16 84V	187310	5.5-6.0-7.0	19	10	23.7	7.9	10.9	1102	44	881	
205/50R16 87V	187710	5.5-6.5-7.5	21	10	24.1	8.3	11.2	1202	44	861	
215/50R16 90V	187850	6.0-7.0-7.5	22	10	24.3	8.9	11.2	1323	44	854	
225/50R16 92V	187720	6.0-7.0-8.0	23	10	24.7	9.1	11.4	1389	44	840	
215/55R17 94H	187770	6.0-7.0-7.5	24	10	26.2	8.8	12.1	1477	44	793	
215/55R17 94V	187760	6.0-7.0-7.5	24	10	26.2	8.8	12.1	1477	44	793	
225/55R17 97T	187430	6.0-7.0-8.0	27	10	26.8	9.2	12.3	1609	44	776	
225/55R17 97V	187420	6.0-7.0-8.0	27	10	26.8	9.2	12.3	1609	44	776	
235/55R17 99H	187830	6.5-7.5-8.5	28	10	27.0	9.4	12.4	1709	44	768	
235/55R17 99V	187790	6.5-7.5-8.5	28	10	27.0	9.4	12.4	1709	44	768	
215/50R17 95V RD	187370	6.0-7.0-7.5	26	10	25.5	8.9	11.9	1521	50	813	
225/50R17 94V	187740	6.0-7.0-8.0	26	10	25.8	9.1	11.9	1477	44	806	
235/50R17 96V	187750	6.5-7.5-8.5	26	10	26.3	9.6	12.1	1565	44	790	
225/45R17 94V RD	187860	7.0-7.5-8.5	24	10	24.9	8.9	11.6	1477	50	834	

RD = Reinforced. Bold designates measuring rim width. Rim protector on 55 and lower aspect ratios. When a V, W or Y appears in the service description, maximum speed capability is as follows: V= 149mph, W= 168mph, Y= 186mph. All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information.