

PROXES® S/T **HIGH-PERFORMANCE CROSSOVER, SPORT TRUCK** **AND SUV RADIAL**

The Proxes S/T is a high-performance tire that delivers a powerful combination of superb handling, confident all-season performance and a smooth, stable ride. The H, V, W and Y speed-rated Proxes S/T offers plus-sizing opportunities on pickup trucks, sport utility vehicles and Original Equipment fitments on high-performance crossover SUVs.

Typical Vehicle Matches

Chevrolet Tahoe, Suburban, C/K pickups; Dodge Durango, Ram; Ford Expedition, F-150 pickups; GMC Yukon, Jimmy, Sierra; Infiniti QX4; Jeep Grand Cherokee; Lexus LX 470; Mercedes-Benz ML320, ML430; Nissan Pathfinder. OE fitments for: VW Toureg; Nissan Murano, FX45; BMW X5; Land Rover.



UTQG
420 A A
Y-Rated sizes
280 A A

| Customer Benefit | Product Features |
|--------------------------|--|
| Wet and Dry Handling | <ul style="list-style-type: none"> • Computer-optimized, unidirectional, all-season tread design • Angled tread grooves • Cap/base tread compound • H, V, W and Y speed-rated |
| Steering Response | <ul style="list-style-type: none"> • Specially engineered polyester casing • High-ply turn-up construction • High bead filler • Two wide, high-tensile steel belts |
| All-Season Performance | <ul style="list-style-type: none"> • Computer-optimized, unidirectional all-season tread design • Double V-shaped tread grooves • Cap/base tread compound • M&S rated |
| Quiet, Stable Ride | <ul style="list-style-type: none"> • Computer-optimized, unidirectional all-season tread design • Jointless bead wire • Jointless cap ply (construction may vary by size) • Two wide, high-tensile steel belts |
| Durability and Long Life | <ul style="list-style-type: none"> • Jointless bead wire • Two wide, high-tensile steel belts • Cap/base tread compound • Rim protector |
| Sporty Appearance | <ul style="list-style-type: none"> • Wide, low-profile design • Ultra-modern sidewall styling • Aggressive, unidirectional all-season tread design |



PROXES® S/T HIGH-PERFORMANCE CROSSOVER, SPORT TRUCK AND SUV RADIAL



| Tire Size | Product Code | Approved Rim Width Range (inch) | Tire Weight (lbs.) | Tread Depth (3/32") | Inflated Dimension | | Static Loaded Radius (inch) | Max. Load (lbs.) | Max. Pressure (PSI) | Revs Per Mile | Price |
|--------------------|--------------|---------------------------------|--------------------|---------------------|-------------------------|----------------------|-----------------------------|------------------|---------------------|---------------|-------|
| | | | | | Overall Diameter (inch) | Overall Width (inch) | | | | | |
| P275/60R15 107H | 242100 | 7.5-8.0-9.5 | 30 | 11 | 28.0 | 11.0 | 12.5 | 2149 | 44 | 744 | |
| 245/70R16 107V | 242660 | 6.5-7.0-8.0 | 34 | 11 | 29.6 | 9.7 | 13.3 | 2149 | 44 | 702 | |
| 265/70R16 112V | 242670 | 7.0-8.0-9.0 | 39 | 11 | 30.7 | 10.3 | 13.7 | 2469 | 44 | 676 | |
| 275/60R16 109V | 242180 | 7.5-8.0-9.5 | 40 | 11 | 29.0 | 11.0 | 13.0 | 2271 | 44 | 720 | |
| 235/65R17 104V | 242640 | 6.5-7.5-8.5 | 31 | 10 | 28.9 | 9.4 | 13.2 | 1984 | 44 | 718 | |
| 305/60R18 120V | 242290 | 8.5-9.0-11.0 | 47 | 12 | 32.4 | 12.0 | 12.6 | 3086 | 44 | 645 | |
| 255/55R18 109V RD | 242160 | 7.0-8.0-9.0 | 34 | 11 | 29.0 | 10.4 | 13.3 | 2271 | 50 | 718 | |
| 275/55R18 114V RD | 242480 | 7.5-8.5-9.5 | 39 | 11 | 29.8 | 11.1 | 13.6 | 2601 | 50 | 696 | |
| 255/50R18 106V RD | 242470 | 7.0-8.0-9.0 | 34 | 11 | 27.9 | 10.2 | 12.9 | 2094 | 50 | 744 | |
| 285/50R18 109V | 242610 | 8.0-9.0-10.0 | 37 | 11 | 29.1 | 10.4 | 13.3 | 2271 | 44 | 715 | |
| 255/45R18 99V | 242590 | 8.0-8.5-9.5 | 30 | 10 | 27.1 | 10.0 | 12.5 | 1709 | 44 | 767 | |
| 295/45R18 108V | 242280 | 9.5-10.0-11.0 | 39 | 11 | 28.5 | 11.7 | 13.0 | 2205 | 44 | 733 | |
| 275/45R19 108Y RD* | 242580 | 8.5-9.0-10.5 | 34 | 10 | 28.8 | 10.7 | 13.3 | 2205 | 50 | 722 | |
| 285/45R19 107V | 242570 | 9.0-9.5-10.5 | 35 | 11 | 29.1 | 11.2 | 13.4 | 2149 | 44 | 714 | |
| 275/55R20 117V RD | 242800 | 7.5-8.5-9.5 | 41 | 11 | 31.9 | 11.0 | 14.6 | 2833 | 50 | 652 | |
| 255/50R20 109V RD | 242490 | 7.0-8.0-9.0 | 31 | 11 | 29.9 | 10.2 | 13.9 | 2271 | 50 | 694 | |
| 285/50R20 116V RD | 242710 | 8.0-9.0-10.0 | 42 | 11 | 31.1 | 11.6 | 14.3 | 2756 | 50 | 669 | |
| 305/50R20 120V RD | 242350 | 8.5-9.5-11.0 | 45 | 11 | 32.1 | 12.4 | 14.6 | 3086 | 50 | 651 | |
| 325/50R20 120V | 242340 | 9.0-10.0-11.5 | 49 | 12 | 32.8 | 13.2 | 12.7 | 3086 | 44 | 636 | |
| 255/45R20 105V RD | 242450 | 8.0-8.5-9.5 | 33 | 11 | 29.1 | 10.1 | 13.5 | 2039 | 50 | 714 | |
| 265/45R20 108V RD | 242560 | 8.5-9.0-10.0 | 34 | 10 | 29.4 | 10.5 | 13.7 | 2205 | 50 | 707 | |
| 295/45R20 114V RD | 242320 | 9.5-10.0-11.0 | 40 | 11 | 30.5 | 11.7 | 14.1 | 2601 | 50 | 683 | |
| 255/40R20 101V RD | 242700 | 8.5-9.0-10.0 | 30 | 10 | 28.0 | 10.1 | 13.1 | 1819 | 50 | 743 | |
| 295/40R20 106V | 242510 | 10.0-10.5-11.5 | 36 | 10 | 29.2 | 11.7 | 13.6 | 2094 | 44 | 711 | |
| 325/50R22 120V | 242680 | 9.0-10.0-11.5 | 61 | 11 | 34.7 | 13.0 | 15.9 | 3086 | 44 | 599 | |
| 285/45R22 114V RD | 242690 | 9.0-9.5-10.5 | 42 | 11 | 32.2 | 11.2 | 15.0 | 2601 | 50 | 645 | |
| 305/45R22 118V RD | 242370 | 9.5-10.0-11.5 | 48 | 11 | 32.8 | 12.0 | 15.2 | 2910 | 50 | 636 | |
| 265/40R22 106V RD | 242460 | 9.0-9.5-10.5 | 45 | 11 | 30.4 | 10.7 | 14.3 | 2094 | 50 | 684 | |
| 305/40R22 114V RD | 242390 | 10.0-10.5-12.0 | 45 | 11 | 31.6 | 12.3 | 14.7 | 2601 | 50 | 657 | |
| 285/35R22 106W RD | 242750 | 9.5-10.0-11.0 | 37 | 11 | 29.8 | 11.3 | 14.0 | 2094 | 50 | 697 | |
| 315/30R22 107Y RD* | 242830 | 10.5-11.0-11.5 | 37 | 11 | 29.5 | 12.2 | 13.9 | 2149 | 50 | 704 | |
| 285/35R23 107V RD | 242500 | 9.5-10.0-11.0 | 40 | 11 | 30.9 | 11.3 | 14.6 | 2149 | 50 | 671 | |
| 325/45R24 120V | 242730 | 10.0-11.0-12.0 | 54 | 11 | 35.4 | 12.6 | 16.4 | 3086 | 44 | 588 | |
| 285/40R24 112V RD | 242720 | 9.5-10.0-11.0 | 46 | 11 | 32.9 | 11.3 | 15.5 | 2469 | 50 | 631 | |
| 305/30R26 109V RD | 242850 | 10.5-11.0-11.5 | 45 | 11 | 33.1 | 12.1 | 15.8 | 2271 | 50 | 628 | |

* UTQG rating is 280 A A, summer tires only, not M&S rated. RD = Reinforced. Rim protector on all sizes. Bold designates measuring rim width. When a V, W or Y appears in the service description, maximum speed capability is as follows: V= 149mph, W= 168mph, Y= 186mph. All Toyo brand tires are subject to continuous development. Toyo Tire (U.S.A.) Corporation reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo dealer or Toyo Tires for current information. See Toyo Safety Advisory for Lifted Light Trucks, Page 40